



HSINSOU CA-600

Carrier for high or low temp. dyeing

HSINSOU CA-600 is an excellent leveling agent for dyeing of polyester and polyester blends at atmospheric temperatures or in pressure dyeing. It is suitable for all types of dyeing equipment including jet dyeing machines. Due to its excellent leveling and migrating properties, CA-600 is especially effective for eliminating barre effects and for repair of faulty dyeing.

General properties:

Appearance	:	Light yellow clear liquid
Composition	:	Phenyl derivatives compound
Ionic nature	:	Nonionic/anionic
pH (1% solution)	:	6.0 +/- 1.0
Solubility	:	Self emulsifiable in water to form a white emulsion

Special features:

1. Suitable for rapid dyeing procedures.
2. Excellent migration properties, minimizing barre effects.
3. Self-emulsifiable to form stable emulsion.

4. No residual odor on fabric with low toxicity.
5. Excellent color yield.
6. Low foaming properties.

Application:

Amount of product required depends of depth of shade and severity of barre condition.

1. For normal dyeing:

Dyes	X%(o.w.f)
HSINSOU SW-BST	1 ~ 2 g/l
HSINSOU CA-600	0.3 ~ 0.6 g/l
HSINSOU AZ-340	0.5 ~ 1 g/l
pH	5 ~ 5.5
Temp. ×Time	130°C×45min

2. For eliminating barre effect:

Add dyes	5% ~ 10%
HSINSOU SW-BST	1 ~ 2 g/l
HSINSOU CA-600	0.6 ~ 1.2 g/l
HSINSOU AZ-340	0.5 ~ 1 g/l
pH	5 ~ 5.5
Temp. ×Time	135°C×60min

3. For stripping :

HSINSOU CA-600	1.2 ~ 1.8 g/l
(NaOH)	pH 9 ~ 12
Temp. ×Time	130°C×45min

Note: full evaluation is recommended prior to commercial usage.